

BEST AVAILABLE COPY

CLAIMS

What is claimed is:

- Sub B1
- 5 1. An animal feed apparatus comprising in combination: a circular container having a peripheral sidewall closed at by a bottom panel thereof, and at a top end thereof an outwardly extending integral lip; an interior surface of the sidewall formed with an inwardly directed slope, and a lid providing an annular lid lip having a pair of annular, outwardly facing and outwardly extending, spaced apart ribs positioned for intimate frictional contact with the sloped sidewall of the container and adapted for vacuum engagement with the container so as to seal an interior space of the container.
- 10 2. The apparatus of claim 1 further comprising a side handle including an outwardly extending portion integral with the lip of the container and a downwardly extending portion spaced apart from the peripheral sidewall.
- 15 3. The apparatus of claim 2 wherein the side handle provides plural stiffening ribs.
4. The apparatus of claim 2 wherein the side handle is adapted for receiving a fence rail frictionally sandwiched between the downwardly extending portion and the container sidewall and wherein the outwardly extending portion includes a fastening aperture adapted for receiving a fastener for securement of the handle to the fence rail.
- 20 5. The apparatus of claim 1 wherein the interior surface has a mirror finish adapted for inhibiting microorganism lodging.
6. The apparatus of claim 1 further comprising a pair of handle receivers placed in opposing positions and integral with the lip of the container, the receivers each downwardly extending and forming a downwardly directed receiving slot.
- 25 7. The apparatus of claim 5 further comprising a strap handle providing at each end of the strap handle, a shaft adapted for engaging the receiving slot, the shaft terminating with a restraining flange.
8. The apparatus of claim 6 wherein each of the shafts are asymmetrical such that the shafts are engagable with the receiving slots when the handle is positioned adjacent to the lip of
- 7 7

the container, the shafts being thereafter not disengagable from the receiving slots when the handle is rotated to a position aligned axially with the container.

- 5 9. The apparatus of claim 2 wherein the side handle is engaged with a fence rail frictionally sandwiched between the downwardly extending portion of the side handle and the container sidewall, the outwardly extending portion including a fastening aperture adapted for receiving a fastener for securement of the handle to the fence rail.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100

101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200